

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 August 2005 (18.08.2005)

PCT

(10) International Publication Number
WO 2005/076200 A1

(51) International Patent Classification⁷: **G06K 15/12**,
B41J 2/47, H04N 1/047, G02B 26/10

[IL/IL]; 10/5 Beri Street, 76352 Rehovot (IL). **BREEN, Craig** [IL/IL]; 16 Ezra Street, 76201 Rehovot (IL).

(21) International Application Number:
PCT/IL2004/000118

(74) Agents: **FENSTER, Paul** et al.; Fenster & Company, Intellectual Property 2002 LTD., P. O. Box 10256, 49002 Petach Tikva (IL).

(22) International Filing Date: 5 February 2004 (05.02.2004)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): **HEWLETT-PACKARD DEVELOPMENT COMPANY, L.P.** [US/US]; 20555 S.H. 249, Houston, TX 77070 (US).


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **LIVNE, Haim** [IL/IL]; 36/17 Rothschild Street, 44449 Kfar Saba (IL). **GREENBERG, Abraham** [IL/IL]; 25/33 Bernstein Street, 75503 Rishon Lezion (IL). **PLOTKIN, Michael**

[Continued on next page]

(54) Title: HIGH PERFORMANCE DYNAMIC MIRROR



(57) Abstract: An imager comprising a photosensitive surface; a light source which produces at least one scanning light beam (111) ; a deflector (112), arranged to deflect the at least one scanning light beam onto the photosensitive surface (108) ; and a sensor (222) which measures the orientation of the deflector (112) . The imager also comprises a controller (120) operative to determine a placement error of said at least one scanning beam (111) on the photosensitive surface (108) , responsive to the orientation measurement by the sensor (222) ; and an actuator, responsive to the displacement error, and arranged to change the direction of deflection of the at least one light beam by the deflector. The sensor (120) is configured to measure the orientation of the deflector (112) substantially at a null in a vibrational mode of the deflector.

WO 2005/076200 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.